

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** SOBO POWER**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** PC35: Washing and cleaning products (including solvent based products).**1.3. Details of the supplier of the safety data sheet****Company name:** Rydlyme International Pty Ltd

3/11 Blaikie Street

Myaree

Western Australia

WA 6154

Australia

Tel: +61 8 9333 0777**Email:** keith@rydlyme.com.au**1.4. Emergency telephone number****Emergency tel:** +61 8 9333 0777

(office hours only)

Section 2: Hazards identification**2.1. Classification of the substance or mixture****Classification under CLP:** Eye Dam. 1: H318; Skin Irrit. 2: H315**Most important adverse effects:** Causes skin irritation. Causes serious eye damage.**2.2. Label elements****Label elements:****Hazard statements:** H315: Causes skin irritation.

H318: Causes serious eye damage.

Signal words: Danger**Hazard pictograms:** GHS05: Corrosion**Precautionary statements:** P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

SAFETY DATA SHEET

SOBO POWER

Page: 2

contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor/.

P332+313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PRIMARY ALCOHOL ETHOXYLATE - REACH registered number(s): 01-2119980051-45-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	68439-45-2	-	Eye Dam. 1: H318; Acute Tox. 4: H302	5-10%

ALKYLPOLYGLYCOSIDE C9-11

603-654-0	132778-08-6	-	Eye Dam. 1: H318	1-5%
-----------	-------------	---	------------------	------

DISODIUM METASILICATE - REACH registered number(s): 01-2119449811-37-XXXX

229-912-9	6834-92-0	-	Skin Corr. 1B: H314; STOT SE 3: H335	1-5%
-----------	-----------	---	--------------------------------------	------

2-(2-BUTOXYETHOXY)ETHANOL - REACH registered number(s): 01-2119475104-44

203-961-6	112-34-5	-	Eye Irrit. 2: H319	1-5%
-----------	----------	---	--------------------	------

SODIUM HYDROXIDE - REACH registered number(s): 01-2119982981-22

215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-5%
-----------	-----------	---	---------------------	------

Non-classified ingredients:

WATER

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	7732-18-5	-	-	60-80%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

[cont...]

SAFETY DATA SHEET

SOBO POWER

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET

SOBO POWER

Page: 4

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	67.5 mg/m ³	101.2 mg/m ³	-	-

SODIUM HYDROXIDE

UK	-	2 mg/m ³	-	-
----	---	---------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale green

Odour: Barely perceptible odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Highly soluble

Viscosity: Non-viscous

Boiling point/range°C: 100

Flash point°C: >93

Vapour pressure: ~14.0mmHg

[cont...]

SAFETY DATA SHEET

SOBO POWER

Page: 5

Relative density: 1.07

pH: >11.4

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

PRIMARY ALCOHOL ETHOXYLATE

DERMAL	-	LD50	>2000	mg/kg
ORAL	-	LD50	>300, <2000	mg/kg

ALKYLPOLYGLYCOSIDE C9-11

ORAL	-	LD50	2000	mg/kg
------	---	------	------	-------

DISODIUM METASILICATE

ORL	MUS	LD50	770	mg/kg
ORL	RAT	LD50	1153	mg/kg

[cont...]

SAFETY DATA SHEET

SOBO POWER

Page: 6

2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

PRIMARY ALCOHOL ETHOXYLATE

ALGAE	LL/EL/IL50	>100	mg/l
Daphnia magna	LL/EL/IL50	1-10	mg/l
FISH	LL/EL/IL50	1-10	mg/l

ALKYLPOLYGLYCOSIDE C9-11

FISH	96H LC50	10	mg/l
------	----------	----	------

DISODIUM METASILICATE

ALGAE	96H LC50	>1000	mg/l
DAPHNIA	48H EC50	4857	mg/l
FISH	96H LC50	3185	mg/l

[cont...]

SAFETY DATA SHEET

SOBO POWER

Page: 7

2-(2-BUTOXYETHOXY)ETHANOL

Daphnia magna	48H EC50	>1000	mg/l
FISH	96H LC50	2700	mg/l

SODIUM HYDROXIDE

DAPHNIA	48H EC50	40.4	mg/l
Gambusia affinis	96H LC50	125	mg/l
Photobacterium phosphoreum	15min LC50	22	mg/l
Poecilia reticulata	24H LC50	145	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

[cont...]

SAFETY DATA SHEET

SOBO POWER

Page: 8

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.